

# LINNA



## BLOCKOUT

Roller Blind Applications

## COLOUR RANGE

### Blockout



Armour



Kendo




Gravel



Bronco



Raw



Buff



Icing

Note: Colours are as accurate as the printing process allows

# LINNA

Linna is a fabric range that has a detuned geometric pattern, and has a micro-scaled pattern which has a subtle sheen that transforms the raw fabric feel to a modernised impression. The subtle sheen, mixed with an on-trend colour palette in blackout opacity, allows for a complete stylish solution throughout the home.

## Features & Benefits

### Opacity

7 Blockout colours

### Made in Australia

Proudly made in Australia to support the local textile industry.

### UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

### 5 Year Warranty\*

Hunter Douglas fabrics are backed by a 5 Year Warranty for your peace of mind.

## Technical Specifications

### Composition

100% Polyester

### Fabric Weight

Blockout 416 gsm +/- 30gsm

### Fabric Thickness

Blockout 0.68 +/- 0.10mm

### Colour Fastness

5 UV

## Care and Cleaning

### General Care

Dusting with a feather duster is all that is require to keep your fabric looking good.

## Solar Optical Guide

SOLAR OPTICAL PROPERTIES							G-TOT				
COLOUR	HEAT PROPERTIES			VISIBLE LIGHT PROPERTIES			GLAZING AND FABRIC				
	TS	RS	AS	TL	RL	AL	G-VALUE	GLAZING A	GLAZING B	GLAZING C	GLAZING D
Foam	0	75	25	0	83	17	6.5	27.5	31.1	32.4	24.1
Bronco	0	75	25	0	83	17	6.5	27.4	31	32.3	24
Kendo	0	74	26	0	82	18	6.6	27.8	31.4	32.6	24.1

### Solar Optical Properties Guide

<b>TS</b>	Heat Transmittance (%)
<b>RS</b>	Heat Reflectance (%)
<b>AS</b>	Heat Absorbance (%)
<b>TL</b>	Light Transmittance (%)
<b>GTOT</b>	% of solar energy transmitted through the blind and glazing

### GTOT Glazing Guide

<b>GLAZING A</b>	Clear single glazing (4mm float)
<b>Glazing B</b>	Clear double glazing (4mm float + 12mm space + 4mm float)
<b>Glazing C</b>	Clear double glazing with argon (4mm float + 16mm space + 4mm float)
<b>Glazing D</b>	Coated double glazing with argon (4mm float + 16mm space + 4mm float)

### GTOT (Range 0-1)

The Solar Heat Gain Coefficient (SHGC), measures the window's (fabric and glass) ability to transmit solar energy into the room. The SHGC is commonly referred to as the g-tot. SHGC/g-tot is a calculation of the g-values of the solar protection device (fabric) and the glazing (A, B, C, D). The lower the GTOT value, the greater its ability to Insulate against solar heat build-up.