


Colour Range











Blockout Fabric



Dayton Blockout

Technical Information

Opacity Blockout

 Composition:
 100% Polyester

 Thickness:
 $0.61 \text{ mm} \pm 10\%$

 Weight:
 $324 \text{ gsm} \pm 10\%$

 Cutting':
 Ultrasonic Cut

Colourfastness: 5-6 Blue Scale (AS 2001.4.21)

Applications Roller Blinds, Panel Glide and Vertical Blinds

Features:



Dayton fabric meets the certification requirements set by Oeko-Tex for the exclusion of harmful substances.

Fire Retardancy Information For NON FR Products^: Suitable for all building classes EXCEPT Class 9(b) entertainment venues. A summary of BCA requirements can be provided on request.

^ Fabrics which are not FR treated, have been FR tested and have a Flammability result over 6 or fabrics which are not FR treated and have not undergone FR testing.

Range:

Item:	Width:	Roll Length:
82.547.xxx	3000 mm	25 metres
82.552.xxx	89 mm	100 metres
82.553.xxx	127 mm	100 metres

Care & Cleaning

Dusting with a feather duster is all that is required to keep your fabric looking good. For the removal of stains, dirt and grime, gently wipe fabric skins with a sponge soaked in lukewarm water. If marks are still visible, add a little detergent. Then dry gently with a clean cloth. Test in inconspicuous area before spot cleaning.

5 Year Warranty#

Turnils Collage fabrics are backed by a 5 year warranty for your peace of mind.

For more information contact our customer service team or visit: hunterdouglas.com.au/enquiry

turnilscollage.com.au