

Plaza

5
FIVE YEAR
FABRIC
WARRANTY

Colour Range



Internal Blockout Fabric

Roller Blind | Panel Glide | Vertical Blind
89mm, 100mm, 127mm, 2.5m & 3.0m

Plaza

Technical Information

Blockout

| | |
|------------------------|---------------------------------|
| Composition: | 100% Polyester |
| Thickness: | 0.32 mm ± 10% |
| Weight: | 320 gsm ± 10% |
| Cutting*: | Ultrasonic, Knife Cut, Aeronaut |
| Colourfastness: | 6-7 Blue Scale (AS 2001.4.21) |

Features:



Oeko-Tex® certified



Plaza has been tested and is Greenguard® Gold Certified to meet strict certification criteria for low Volatile Organic Compound (VOC) emissions and is acceptable for use in environments such as schools and healthcare facilities (IEQ-11).

Fire Retardancy Information for NON FR Products[^]:

Suitable for all building classes **except** Class 9(b) entertainment venues. A summary of BCA requirements can be provided on request.
[^]Fabrics which are not FR treated, have been FR tested and have a Flammability result over 6 or fabrics which are not FR treated and have not undergone FR testing.

| Range: | Item: | Width: | Roll Length: |
|--------|------------|--------|--------------|
| | 82.541.OXX | 2500mm | 25 metres |
| | 82.542.OXX | 3000mm | 25 metres |
| | 82.151.OXX | 89mm | 100 metres |
| | 82.152.OXX | 100mm | 100 metres |
| | 82.153.OXX | 127mm | 100 metres |

Care & Cleaning Dusting with a feather duster is all that is required to keep your fabric looking good. For the removal of stains, dirt and grime, gently wipe fabric skins with a sponge soaked in lukewarm water. If marks are still visible, add a little detergent. Then dry gently with a clean cloth. Test in inconspicuous area before spot cleaning.

For more information contact our customer service team or visit: hunterdouglas.com.au/enquiry

turnilscollage.com.au